


Circle Valve Technologies Inc.

1533 Gehman Road
Harleysville, PA 19438

Toll Free: 800-645-6733

Phone: 267-933-6300

Fax: 267-933-6305

Email: sales@circlevalve.com

Item # 1335BA4AT-24VDC, 2 Way Solenoid Valves

List Price

-

\$145.20
Features

- Normally closed and normally open
- Direct acting. No minimum differential pressure to operate
- Brass, iron, and stainless steel body. Applications
- Instrumentation. Laboratory
- Burner pilot for gas and oil
- Welding equipment. Humidifiers


Specifications

Series	1335
Valve Type	Normally Closed
Body Material	Brass
Diaphragm Type	Hung Diaphragm
Port Size	1/2 in
Operating Pressure	0 to 105 psig 0 to 7 bar
Max. Temperature	176 °F 80 °C
Orifice Size	.55 in 14 mm
Flow Coefficient (Cv)	3.10

Seat Material	Buna N
Voltage	24 VDC
Coil Type	MH19C
Coil VA Inrush Amperage	19
Coil VA Holding Amperage	19
Options	Y - Weather proof housing. YC - Water, weather and saline corrosion proof coils. Z - Explosion and weather proof housing. ZC - Explosion and weather proof coils.
Weight	1.75 lbs
Dim. B	3.15 in 80 mm
Dim. B1	3.46 in 88 mm
Dim. C	.59 in 15 mm
Dim. D	2.01 in 51 mm
Dim. E	2.36 in 60 mm
Dim. F	2.09 in 53 mm
Dim. G	3.35 in 85 mm
Dim. H	1.02 in 26 mm
Dim. I	2.24 in 57 mm
Dim. J	.87 in 22 mm
CVT Item #	1335BA4AT