



PRODUCT PART NUMBER →			V-570SCJ
ITEM	DESCRIPTION	PRESS. TEMP. →	10000 PSI @ 200°F 8000 PSI @ 450°F MAX
1	Valve Body	(S)	ASTM A479-316
2	Ball Seat (2)	(C)	CARBIDE BALL
3	Stem Seal (2)	(J)	TPC w/FLRSLCN O-RING
4	Stem (2)		ASTM A479-316
5	Bonnet (2)		ASTM A479-316
6	Handle Assembly (2)		ASTM A582 18-8
7	Seal Retainer (2)		ASTM A479-316

NOTES

1. DIMENSIONS IN [] ARE IN MILLIMETERS.
2. APPROX. WEIGHT 3.0 lbs. (1.4 kg.)
3. <ZC> INDICATES ZINC COBALT PLATED WITH DICHROMATE DIP.
4. <P0> INDICATES PHOSPHATE AND OIL.
5. <P0> AISI 1018 C.S. IS USED WHEN WELDED BODY CONNECTION ARE SPECIFIED.
6. 316 SS MANIFOLD/VALVE MEETS REQUIREMENTS OF NACE MR0175 (LATEST REV.) UP TO 140° F.

PGI RESERVES THE RIGHT TO CHANGE THE DESIGN, DIMENSIONS OR MATERIAL CONTENT OF OUR PRODUCTS WITHOUT PRIOR NOTIFICATION.

PGI INTERNATIONAL

16101 VALLEN DRIVE (713) 466-0056 or 1-800-231-0233
HOUSTON, TX. 77041 FAX: (713) 744-9892

2 VALVE BLOCK & BLEED
1/2" MNPT x 1/2" FNPT

REVISION DATE	CAD#	DRAWING NO.	REVISION LEVEL
6-25-03	SCALE NTS	V-570SCJ	2

GENERAL PRODUCT DESCRIPTION

PGI EXTERNAL DOCUMENT