The SE/ST series junction box provides a compact design and heavy duty housing for remote electrical indication of linear valve/actuator position. The wide variety of options make the SE/ST series perfect for use in IP65 weather proof. SOLDO has the flexibility and know how to offer an effective support whenever specific needs require the development of customised solutions.

# (WEATHER PROOF)

IP65 weather proof enclosure.

### ( CORROSION RESISTANT AND HEAVY DUTY HOUSING )

The SE/ST series junction boxes are manufactured in a heavy duty housing. The SE is made of die cast dichromated and polyester powder coated aluminium. The ST series is made of 316 stainless steel.

# (STANDARDIZED MOUNTING)

Housing conforms to international dimension standards ISO FO5 bolt hole locations. A complete range of stainless steel mounting kit to fit SE on pneumatic actuators.

### (COST ADVANTAGE)

The SE/ST series junction BOX is a cost effective alternative to field wiring. The full system with the switches installed will come ready for use. Field mount and you are ready to go.

### (JUNCTION BOX OPTION)

The SE/ST series can be provide with extra terminal strip to accommodate external solenoid valve and has two 1/2" npt cable entries (The SE also has the option of having an extra 2 cord grips or 1/2" npt hubs shown below]. This feature provides a significant cost saving by eliminating the need for a separate junction box and associated labor. Cable entries have a 13 mm thread thickness. This feature prevents housing demage due to very heavy cables or cable glands.

#### (MATERIALS)

SE Body and cover: die cast polyester powder coated aluminium ST Body and cover: 316 stainless steel (CF8M) : stainless steel Fasteners Seal · FPDM

### (RATINGS)

Temperature range: standard 32°F(-20°C) to 176°F(80°C)







SE Shown with "2H" connection option

NTROL

BULLETIN NUMBER: PS00097-04

#### SOLDO USA LLC

10178 International Blvd. - Cincinnati. Ohio 45246 tel. (513) 860-5465 - fax (513) 860-5464 e-mail: usa@soldo.net

55

soldo.net }

### (SOLDO LINEAR AS-i PACKAGE)

The SOLDO Linear AS-i package is made especially for linear valves with no special linkages or mounting hardware required. The system has a junction box with 2 proximity sensors for indication of open and closed position. Optional local LED's are available for visual indication. The system uses the "BOLT" series proximity sensor that has been a proven standard in the industry for over 10 years!

The AS-i card that is used is the SOLDO standard card with 4 inputs and 3 outputs. Now for the first time, a true Linear AS-i Package that makes installation and hookup a breeze!



# (STANDARD OPTIONS AVAILABLE - Nomenclature)



10178 International Blvd. - Cincinnati, Ohio 45246 tel. (513) 860-5465 - fax (513) 860-5464 e-mail: usa@soldo.net