



PRODUCT PART NUMBER		V-506SCJ	
NO.	DESCRIPTION	10,000 PSI @ 200° F 1,000 PSI @ 450° F MAX	QTY.
1	VALVE BODY	(S) ASTM A479-316	1
2	BALL (1/4")	(C) CARBIDE BALL	1
3	STEM SEAL	(J) TPC w/FLRSLCN	1
4	STEM	ASTM A479-316	1
5	BONNET	ASTM A479-316	1
6	SEAL RETAINER	ASTM A479-316	1
7	HANDLE ASSEMBLY	300 SERIES SS	1
8	ROLL PIN	300 SERIES SS	1

NOTES	
1.	DIMENSIONS IN [ ] ARE IN MILLIMETERS.
2.	APPROX. WEIGHT X.X lbs. (X.X kg.)
3.	<AZ> INDICATES ALKALINE ZINC PLATED WITH DICHROMATE DIP.
4.	<PO> INDICATES PHOSPHATE AND OIL.
5.	<P0> AISI 1018 C.S. IS USED WHEN WELDED BODY CONNECTION ARE SPECIFIED.
6.	316 SS MANIFOLD/VALVE MEETS REQUIREMENTS OF NACE MR0175 (LATEST REV.) UP TO 140 °F
OPTION CODES	
<b>SEE PROPOSAL FOR EXPIRATION DATE</b>	

PROPOSAL#	<input type="text"/>
PROPOSAL DATE	<input type="text"/>
PROJECT	DR 1008-02
CUSTOMER	EDMONTON
<b>1/2" M-F HARD SEAT VALVE</b>	
<b>PGI International</b> HOUSTON, TEXAS	
CAD NO.	V-506SCJ
<b>CUSTOMER PRODUCT PROPOSAL</b>	
<b>PGI EXTERNAL DOCUMENT</b>	