

T24-Hx

HANDHELD RADIO RECEIVER WITH DISPLAY

The WIRELESS-T24-HS, WIRELESS-T24-HA and WIRELESS-T24-HR are handheld indicators



Features

- Frequency : 2.4 GHz
- License : Exemption
- Range : up to 800 m open field
- Antenna : Integrated
- High resolution : 7 digits
- Channels : WIRELESS-T24-HS : 1
WIRELESS-T24-HA : up to 12
WIRELESS-T24-HR : unlimited (roaming)
- Option : Leather carry case with clear viewing window and shoulder strap (CASE-PSD)

Applications

WIRELESS-T24-HS, -HA and -HR of SENSY are perfectly designed to the following applications

- Display of force or torque from transducer installed on a mobile equipment
- Remote display of the load lifted by a crane.

Functions

- WIRELESS-T24-HS provides a point to point connection to a single transmitter.
- WIRELESS-T24-HA provides either a summed total from all selected transmitters and the ability to view individual transmitters.
- WIRELESS-T24-HR is a roaming handheld allowing the operator to cycle the display between all transmitters within its range.
- Reset (tare) by push button
- Auto "power off" and "power on" of remote transmitter module

Specifications	T24-HS	T24-HA	T24-HR	
Type	Handheld indicator (1 sensor)	Handheld indicator (up to 12 sensors)	Handheld indicator (unlimited (roaming))	-
Display	7 digits LCD of 8.8 mm high	7 digits LCD of 8.8 mm high	7 digits LCD of 8.8 mm high	-
Power supply	2.5 up to 3.6 VDC (2 AA alkaline batteries)	2.5 up to 3.6 VDC (2 AA alkaline batteries)	2.5 up to 3.6 VDC (2 AA alkaline batteries)	-
Autonomy @ normal mode (2 batteries)	35 hours	35 hours	35 hours	-
Autonomy @ "Powered off" mode	18 months	18 months	18 months	-
Service temperature range	-10..+50	-10..+50	-10..+50	C
Storage temperature range	-40..+85	-40..+85	-40..+85	C
IP Rating	IP67 / NEMA 4	IP67 / NEMA 4	IP67 / NEMA 4	-
Dimensions	152 x 90 x 34 mm	152 x 90 x 34 mm	152 x 90 x 34 mm	mm

Specifications subject to change without notice