



PRODUCT PART NUMBER →			V-572CCT	V-572SCT
ITEM	DESCRIPTION	PRESS. TEMP. →	10,000 PSI @ 200° F MIN. 8,000 PSI @ 450° F MAX.	10,000 PSI @ 200° F MIN. 8,000 PSI @ 450° F MAX.
1	Body	(C)	<ZC>ASTM A108-1215	(S) ASTM A479-316
2	Ball Seat (2)	(C)	CARBIDE BALL	(C) CARBIDE BALL
3	Stem Seal (2)	(T)	TEFLON PRESSURE CORE	(T) TEFLON PRESSURE CORE
4	Stem (2)		ASTM A479-316	ASTM A479-316
5	Bonnet (2)		<ZC>ASTM A108-1215	ASTM A479-316
6	Handle Assembly (2)		<ZC>ASTM A108	ASTM A582 18-8
7	Seal Retainer (2)		ASTM A479-316	ASTM A479-316
8				
9				

NOTES

- DIMENSIONS IN [] ARE IN MILLIMETERS.
- APPROX. WEIGHT 2.5 lbs. (1.14 kg.)
- <ZC> INDICATES ZINC COBALT PLATED WITH DICHROMATE DIP.
- <P0> INDICATES PHOSPHATE AND OIL.
- <P0> AISI 1018 C.S. IS USED WHEN WELDED BODY CONNECTION ARE SPECIFIED.
- 316 SS MANIFOLD/VALVE MEETS REQUIREMENTS OF NACE MR0175 (LATEST REV.) UP TO 140° F.

PGI RESERVES THE RIGHT TO CHANGE THE DESIGN, DIMENSIONS OR MATERIAL CONTENT OF OUR PRODUCTS WITHOUT PRIOR NOTIFICATION.

PGI INTERNATIONAL

16101 VALLEN DRIVE (713) 466-0056 or 1-800-231-0233
HOUSTON, TX. 77041 FAX: (713) 744-9892

2 VALVE BLOCK AND BLEED
3/4" MNPT x 1/2" FNPT

REVISION DATE	CAD#	DRAWING NO.	REVISION LEVEL
6-25-03	SCALE NTS	V-572S	3

PGI EXTERNAL DOCUMENT

GENERAL PRODUCT DESCRIPTION